

## DESCRIPTION

This AC-DC switching power supplies in a package of 2 x 4 inches is a compact Class-II PSU and no load power consumption less than 0.21W. This PSU is capable of delivering 65 watts continuous power at convection cooling and 50°C operation temperature. Product is suitable for audio & video, display, information, and networking application.

## FEATURES

- Class-II design
- Design to meet IEC 60950-1 and IEC 62368-1 safety standard
- Compact dimension 2"x4"x1.047"
- No load power consumption less than 0.21W
- EN 55032 Class B radiated emission
- High altitude 5000 meters operation
- OTP, Brown out protection

## INPUT SPECIFICATIONS

Input voltage:	90-264 VAC
Input frequency:	47-63 Hz
Input current:	1.7 A (rms) for 115 VAC 0.8 A (rms) for 230 VAC
No load power consumption	≤0.21A
Touch current:	250 uA max. @ 264 VAC, 63 Hz

## OUTPUT SPECIFICATIONS

Output voltage/current:	See rating chart.
Total output power:	65W
Ripple and noise:	±1%.
Protection:	
Over voltage	Set at 110~130% of nominal output voltage, auto recovery
Short circuit & overcurrent	Output protected to short circuit condition, auto recovery
Over temperature	Detected by thermistor, auto recovery
Brown out	Set at 70VAC
Temperature coefficient:	All outputs ±0.04% /°C maximum
Transient response:	Maximum excursion of 5% or better on all models, recovering to 1% of final value within 500 us after a 25% step load change

## ENVIRONMENTAL SPECIFICATIONS

Operating temperature:	-20°C to +70°C
Storage temperature:	-40°C to +85°C
Relative humidity:	5% to 95% non-condensing
Derating:	Derate from 100% at +50°C linearly to 50% at +70°C, applicable to convection cooling condition

## FSP065-P24 A Series



RoHS  
CE

## SAFETY STANDARD APPROVAL

CB

IEC 62368-1, IEC 60950-1



UL 62368-1,  
CAN/CSA 22.2 No.62368-1-14

## GENERAL SPECIFICATIONS

Efficiency:	See rating chart.
Power turn on time	1.0 Sec maxi.
Hold-up time:	10 mS minimum @ 100% load & 115 VAC
Line regulation:	±0.5% maximum at full load
Inrush current:	55A @ 115VAC @ 25°C cold start 100A @ 230 VAC @ 25°C cold start
Operating altitude:	5000 meters above sea level
Withstand voltage:	3000 VAC from input to output,
Isolation Resistance:	Input to output 100M ohm @ 500Vdc, 25°C
MTBF:	400,000 hours minimum at full load at 25°C ambient, calculated per BELL CORE SR-332
EMC Performance	
EN55032	Class B conducted, class B radiated
FCC:	Class B conducted, class B radiated
VCCI:	Class B conducted, class B radiated
EN61000-3-2:	Harmonic distortion, class A
EN61000-3-3:	Line flicker
EN61000-4-2:	ESD, ±8 KV air and ±4 KV contact
EN61000-4-3:	Radiated immunity, 3 V/m
EN61000-4-4:	Fast transient/burst, ±1 KV
EN61000-4-5:	Surge, ±1 KV diff, ±2 KV com
EN61000-4-6:	Conducted immunity, 3 Vrms
EN61000-4-8:	Magnetic field immunity, 3 A/m
EN61000-4-11:	Voltage dip immunity, 30% reduction for 500 ms, criteria A >95% reduction for 10 ms, criteria A >95% reduction for 5000 mS, criteria B


## OUTPUT VOLTAGE / CURRENT RATING CHART

Model	Output Voltage	Min. Load	Max. Current	Tolerance	Ripple & Noise <sup>(1)</sup>	Max. Power	Efficiency 115 / 230 Vac
FSP065-P24-A12	12 V	0 A	5.40 A	±3%	120 mV	65W	88 / 89%
FSP065-P24-A19	19 V	0 A	3.42 A	±3%	190 mV	65W	89 / 90%
FSP065-P24-A24	24 V	0 A	2.70 A	±3%	240 mV	65W	90 / 90%
FSP065-P24-A54	54 V	0 A	1.20 A	±3%	300 mV	65W	91 / 92%


### Notes:

(1) Ripple and noise is maximum peak to peak voltage value measured at output within 20 MHz bandwidth, at rated line voltage and output load ranges, and with a 10  $\mu$ F tantalum capacitor in parallel with a 0.1  $\mu$ F ceramic capacitor across the output.


## INPUT VOLTAGE DERATING CURVE



## OUTPUT DERATING CURVE



## MECHANICAL SPECIFICATIONS



### Note:

- IN1: JST B2P3-VH or EQU

Pin 1	Neutral
Pin 2	NC
Pin 3	Line

- CN200: JST B4P-VH or EQU

Pin 1, 2	V+
Pin 3, 4	Return

- Dimension (L\*W\*H):  
101.6 \* 50.8 \* 26.6 mm  
4" \* 2" \* 1.047"

- Weight:  
125 grams. (0.275 lbs.) approx.