



# PC PSU FSP500-60EGN

## DESCRIPTION

This specification describes a 500 watts power supply. With 6 output, and remote ON/OFF control for ATX-12V system and a "Power factor correction (active PFC)" circuit at 100V-240Vac.

## APPLICATION

Desktop

## WATTAGE

**Wattage:** 500W

## DIMENSION

**Dimension:** 140mm(L) x 150mm(W) x 86mm(H)

## PRODUCT HIGHLIGHT

**Efficiency Level:** 80PLUS Gold  
**Erp Lot:** <0.5W  
**Input Voltage:** 100~240Vac

## INPUT SPECIFICATION

**Input Range:** 100-240 Vac  
**Input Frequency:** 47-63 Hz  
**Input Current:** 115V@ < 8.0 Amps - rms  
230V@ < 4.0 Amps - rms

## OUTPUT SPECIFICATION

**Hold up Time:** 115V/60Hz 17mSec.  
Minimum@100% Load,  
+3.3V 20mS (maximum)  
**Output Rise Time:** +5V 20mS (maximum)  
+12 V 20mS (maximum)  
-12 V 20mS (maximum)



## SAFETY STANDARD APPAOVAL



## GENERAL SPECIFICATION

**Efficiency:** 87%@ 20% load; 90%@ 50% load;  
87%@ 100% load  
**PWOK Delay Time:** 500ms > PWOK > 100ms  
**EMC Performance:** EN55022 class B  
EN55024  
EN 61000-3-2  
EN 61000-3-3

## ENVIRONMENTAL SPECIFICATION

**TEMP.Range:** Storage Temperature: -40°C to +70°C  
**MTBF:** The power supply reliability, when calculated by "Bellcore" latest revision are exceed 100,000 hours with all output at maximum load and an ambient temperature of 25°C.

## \*Output Voltage and Current Rating

	+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb
<b>Ripple-Noise(R-P) mV</b>	50mV	50mV	50mV	120mV	200mV	50mV
<b>Regulation Load %</b>	±5%	±5%	±5%	±5%	±10%%	±5%
<b>Output Max.(A)</b>	24A	24A	18A	18A	0.3A	3.5A
<b>Output Min.(A)</b>	0.1A	0.2A	0.1A	0A	0A	0A

## NOTES

(1) +3.3V & +5V total output not exceed 130W.

When +5V is load to 22A, the +3.3V maximum load is 3A.

When +3.3V is load to 24A, the +5V maximum load is 10A.

(2) +12V1 & +12V2 total output not exceed 432W(36A).

(3) All outputs shall be safety-isolated from the AC mains and share a common return. This common return must be connected to supply chassis.

(4) Voltages and ripple are measured at the load side of mating connectors with a 0.1uF monolithic ceramic capacitor paralleled by a 10uF electrolytic capacitor across the measuring terminals.

This content is subject to change, please refer to specification for more detail.  
FSP reserve the right to change the content without prior notice